

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 January 2005 (20.01.2005)

PCT

(10) International Publication Number
WO 2005/006056 A1

(51) International Patent Classification⁷: **G02B 27/22**,
1104N 13/00, G02F 1/1333

(74) Agents: **MERRYWEATHER**, Colin, Henry et al.; J.A.
Kemp & Co., 14 South Square, Gray's Inn, London WC1R
5JJ (GB).

(21) International Application Number:
PCT/GB2004/003000

(22) International Filing Date: **9 July 2004 (09.07.2004)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
0316215.3 **10 July 2003 (10.07.2003)** **GB**

(71) Applicant (for all designated States except US): **OCUTY
LIMITED [GB/GB]**; 77 Heyford Park, Upper Heyford,
Oxfordshire OX25 5HD (GB).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **WOODGATE**,
Graham, John [GB/GB]; 9 Vicarage Road, Hen-
ley-on-Thames, Oxfordshire RG9 1HF (GB). **HAR-**
ROLD, Jonathan [GB/GB]; 8 Robins Grove, Warwick,
Warwickshire CV34 6RF (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **DIRECTIONAL DISPLAY APPARATUS**



(57) Abstract: A birefringent lens structure comprises a birefringent lens array capable of directing light of a given polarisation into a directional distribution, the birefringent lens comprising a solid birefringent material and an isotropic material having an interface having a refractive structure. A switchable liquid crystal layer capable of rotating the polarisation of light passing therethrough is arranged adjacent the first birefringent material. The interface between the birefringent material and the liquid crystal layer has an alignment microstructure providing alignment of the birefringent material and the liquid crystal layer. A pair of electrodes for applying an electric field to switch the liquid crystal are arranged with both the lens array and the switchable liquid crystal layer therebetween and a conductive material is incorporated in the lens array to reduce the voltage drop across the lens array. To reduce reflection, the interface between the birefringent material and the isotropic material has an interface having alignment microstructure providing alignment of the birefringent material, and the refractive index of the isotropic material is substantially equal to the extraordinary refractive index of the birefringent material.

WO 2005/006056 A1